

800-228-8861 502-968-2211 rental.sales@wareinc.com www.wareinc.com

CTOCK EQUIPMENT WARE Offers New/Used Equipment In Stock

BOILER INFORMATION

Manufacturer	Victory Energy	
Year	2019	
Туре	Saturated Steam	
Capacity	250 HP / 8,625 PPH	
Pressure	150 PSI	
Burner	Powerflame CM9A-GO-30	

FUEL CONSUMPTION

Natural Ga	10,461 SCFH	
#2 Oil	74.5 GPH	1
KAN		1
A Contraction		1 1 1 1 1
ELECTR	CAL POWER REQUIREMENTS	
480V, 3	Ph, 60 Hz	No. No.
		1
14		- Marian
TR.		- W

The boiler is offered with a one (1) year parts and motors warranty (less labor) and the pressure vessel is guaranteed to pass an ASME inspection.

CONNECTION SIZES

Main Steam	6" 300# Flanged
Natural Gas	3" NPT
#2 Oil	1" NPT
Feedwater	1-1/2" NPT
Bottom Blowdown	1-1/2" NPT
Continuous Blowdown	1-1/2" NPT

CONTROLS.

Honeywell 7800 Series

EMISSIONS DATA

- NOx .036# / mmBtu w/17% FGR
- so2 .001# / mmBtu
- ^{CO} .15# / mmBtu
- РМ .008# / mmBtu

BOILER OVERALL DIMENSIONS & WEIGHT

Length/Width/Height243" / 85" / 95"Shipping Weight17,000 lbsOperating Weight26,908 lbs



ADDITIONAL INFORMATION

SSB-51 Model: F3-DB-564C-250-S150-SB-FGR

Firetube Boiler, 3-Pass, Dryback, 250 BHP, 150 psig with a Powerflame Low NOx Natural Gas & #2 Oil burner system. Burner has a 6:1 turndown ratio and is rated for 10.5 mmBtu gas input.

Package meets UL & CSD-1 codes.