



INDUSTRIAL PACKAGED STEAM BOILER

Horizontal Drum Sectional Water Tube
30 to 50 HP Gas Fired

104 Steam Boilers 30 to 50 HP

Industrial Packaged
Steam Boiler

Pressures
to 250 PSI



THE PARKER DESIGN

The Parker water tube design offers an extremely efficient, reliable steam boiler built for the long term and ease of maintenance. The Parker design offers many advantages. Compare ours to the competition.

ADVANTAGES

1. Safety

The Parker ASME tube bundle is extremely flexible and offers a long life with a 25 year warranty against thermal shock. No Parker Boiler has ever been known to experience an internal explosion.

2. Large Heating Surface

A large amount of heating surface provides increased efficiency, long boiler life and minimizes chances of scaling. Compare ours to the competition.

3. Simplicity

The Atmospheric Burner System, the control system and entire boiler are furnished so that it is simple to operate by regular personnel. Simplicity is a decided advantage as there are no expensive blowers, complicated controls, or burner adjustments, as is necessary on many boilers.

4. Codes

All Parker Steam Boilers are manufactured in accordance with the ASME Power & Heating Boiler Codes and registered with the National Board of Boiler and Pressure Vessel Inspectors. The standard natural gas fired model is furnished as an Underwriters' Laboratories, Inc. Listed Gas Fired Boiler Assembly and displays their symbol on the nameplate. Outdoor, propane and Low NOx models are ETL listed. Canadian models are C-ETL Listed Industrial and Commercial Gas Fired Packaged Boilers certified to CAN/CGA 1-3.1 and UL 795.

5. Internal Accessibility

Inspection cabinet doors can easily be removed in a matter of minutes, making the internal boiler, drum, tubes, and burners readily accessible. Easy-to-remove gasketed access plugs are provided at both ends of every tube. Boiler inspections can be accomplished quickly and at low costs.

6. Ease of Inspection and Repair

Any boiler may eventually require retubing depending on care and operating conditions. Retubing does not require special tools, skills or welding as is necessary on most boilers. Tubes are reversible and replaceable through the cabinet door.



PARKER BOILER CO.
5930 Bandini Boulevard
Los Angeles, CA 90040
Tel (323) 727-9800
Fax (323) 722-2848
www.parkerboiler.com

BROCHURE 104 111

"Never a Compromise for Quality or Safety"



INDUSTRIAL PACKAGED STEAM BOILER

Horizontal Drum Sectional Water Tube

30 to 50 HP Gas Fired



104 Steam Boilers 30 to 50 HP

Safety Valve

Horizontal steam drum 20" diameter heavy seamless 1/2" thick with extra heavy 1-1/8" flat welded heads. Over 60,000 PSI tensile strength. All drum screwed openings swaged for extra heavy thickness.

Drum inspection openings - both heads

Extra heavy tubes are 1-5/16" OD, 0.12" (11GA) heavy thickness steel

Staggered tubes flexibly designed for free expansion and contraction provide 10 pass self-baffled heating surface.

Drum downcomer leg with inspection cleanout openings with blowoff valves at bottom, both sides.

Heavy Steel Boiler frame for setting on concrete floor

Steam valve

Secondary M.R. probe type low water cutoff


Automatic burner controls include 100% flame safeguard, dual electric gas valves and staged firing on natural gas.

Water level pump control & primary low water cutoff

Tubes are furnished in individual sections each attached by two union connections
30 HP - 3 sections
40 HP - 4 sections
50 HP - 5 sections

Easy to remove tube access plugs on tube headers

Efficient Parker T-type up-shot low pressure gas burners provides high combustion efficiency and uniform distribution.



THE PARKER DESIGN

A time proven product backed by one of the largest and most successful manufacturers of packaged steam boilers whose name is synonymous with quality and safety. Every boiler is thoroughly factory fire tested and is required to meet the highest standards in all phases of mechanical and operating efficiency before shipment.

ADVANTAGES

7. Dry Steam

Our large horizontal steam drum provides ample steam release area to assure dry steam delivery. No steam separators are required.

8. Heavy Duty Tubes

Parker tubes are 1-5/16" O.D., 0.12" (11GA) heavy thickness which is almost double that of standard gauge boiler tubing. Each tube is double-welded to assure a rugged connection.

9. Fast Heat-Up

Our boiler requires less than ten minutes to heat up to 100 PSI from a cold start which is a considerable time and fuel saver.

10. Low Cost Operation

The staggered tubing design provides a 10 pass heating surface to increase efficiency.

11. Heavy Insulated Cabinet

The cabinet is durably constructed with two thicknesses of heavy steel, insulated on all sides with high temperature thermal fiber insulation to effectively reduce heat losses to a minimum.



"Never a Compromise for Quality or Safety"

PARKER BOILER CO.
5930 Bandini Boulevard
Los Angeles, CA 90040
Tel (323) 727-9800
Fax (323) 722-2848
www.parkerboiler.com

BROCHURE 104 111